



RAYCHEM JOINTING SYSTEM MXAW FOR AWA CABLES UP TO 36 KV, WITH MECHANICAL CONNECTORS

KEY FEATURES

- All-inclusive kit
- Short and slim design
- Based on elastomeric triple layer joint sleeves
- No crimping tools or tool maintenance required
- Robust and reliable armor continuity
- Meets HD 629.1 S2

TE Connectivity (TE) through the Raychem product line, offers a comprehensive range of joints for all cable types. The MXAW jointing system is based on a joint design using mechanical connectors and is a well-established component in today's complex underground power distribution networks.

The mechanical connectors supplied with the kit are for conductor and aluminium armour wire. It is due to the shearbolt technology that this system is easy to install as no crimping tool is required when connecting the cables.

TE's Raychem jointing system MXAW provides high levels flexibility especially as the kits are widely range-taking and cover most conductor constructions including their tolerances.

Reliability and performance are essential when it comes to customer demands and the MXAW joints meet this demand by exceeding international performance standards including CENELEC HD 629.1 S2 or IEC 60502-4 for joints.

The short and space-saving design of MXAW is perfect in underground environments where space is limited; bulky waste and costly waste disposal are avoided.

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.

Raychem Jointing System MXAW



TE's Raychem name is synonymous with reliability in extreme environments and conditions. TE's Raychem MXAW cable accessories are designed to withstand environmental extremes over long operating lifetimes and offer easy installation.



PRODUCT SELECTION INFORMATION: DIMENSIONS IN MM

Description	Cross Section Range [mm ²]				Diameter Conductor mm	Diameter Over Core Insulation mm	Diameter Cable Over Sheath mm
	12 kV	17.5 kV	24 kV	36 kV			
MXAW-5131	-	-	95 - 185	-	10.3 - 17.6	23.0 - 31.2	37 - 43
MXAW-5132	-	-	150 - 300	-	12.9 - 21.6	25.8 - 34.6	40 - 48
MXAW-5141	-	-	240 - 400	-	17.8 - 24.6	29.4 - 38.8	44 - 54
MXAW-5151	-	-	500	-	25.5 - 27.6	37.2 - 41.6	48 - 56
MXAW-5161	-	-	630	-	29.0 - 32.5	39.2 - 44.7	50 - 60
MXAW-6131	-	-	-	150 - 300	13.9 - 21.6	31.1 - 39.6	43 - 55

ORDERING INFORMATION

TE Connectivity's MXAW has a very long shelf life and, as a result, simplifies material logistics. This jointing system is based on the standard MXSU design including the cutback dimensions and Rayfit Technology.

te.com/energy

©2016 TE Connectivity Ltd. family of companies. All Rights Reserved. EPP-2793-DDS-6/16

Raychem, TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

FOR MORE INFORMATION: TE Technical Support Centers

USA: +1 800 327 6996
 France: +33 380 583 200
 UK: +44 0870 870 7500
 Germany: +49 896 089 903
 Spain: +34 916 630 400
 Italy: +39 333 250 0915
 Benelux: +32 16 351 731
 Canada: +1 (905) 475-6222
 Mexico: +52 (0) 55-1106-0800
 Latin/S. America: +54 (0) 11-4733-2200
 China: +86 (0) 400-820-6015